



**SIMPLE. DURABLE.
PRECISE.**

QC Series with Ingersoll Rand®
Proven Clutch Design

QC SERIES —————
CLUTCH TOOLS

————— **SIMPLY PRECISE**
CORDLESS PRECISION FASTENING SYSTEMS

QC SERIES

CLUTCH TOOLS

SIMPLY PRECISE



QC Series Clutch Tools are engineered for robust performance and designed to last more than 500k cycles in demanding assembly environments to deliver precision in every fastening application. The clutch tool offers a seamless setup experience via the INSIGHT™ Connect app, enabling quick programming of advanced parameters to meet specific application needs.

Leveraging the Ingersoll Rand® proven clutch design, the QC Series provides accuracy and durability for customer-critical applications. Designed with user comfort and precision in mind, the balanced ergonomic build helps reduce fatigue, while the dual-speed non-contact trigger and a status beam light provide clear feedback for smooth, accurate, and efficient operation.



Easy to Use

- 360° status beam light on Pistol Tools and status beam headlight on Angle Tools
- Advanced programmable parameters using the INSIGHT™ Connect Mobile App
- Single battery platform IQV20™ cordless platform



Built to Last

- Lasts up to 500k cycles in a high-speed assembly environment



Work with Accuracy

- Proven clutch design achieves Cmk >1.67 at +/- 10% accuracy
- Lockable, tamper-proof clutch delivers up to 30 Nm of torque
- Programmable RPM helps tune the tool to meet application-specific requirements

QC SERIES FEATURES




Advanced Parameters

- Rundown and Tightening Speed
- Tightening Direction
- Reverse Disable
- Cycle Delay
- Soft Start
- Rehit Detection
- Shiftdown Condition



Improve Uptime and Productivity with Advanced Programmable Parameters

QC Series Clutch Tools allow users to easily configure advanced programmable parameters to tailor the tool for each specific application. Adjustable torque output, programmable speed control and other advanced parameters streamline operations, reducing downtime and improving productivity, even on the most complex jobs.



Stay in Control of your Fastening Processes with the INSIGHT™ Connect App


Tool setup and advanced programming is intuitive in the INSIGHT™ Connect App. Easily program the QC Series tools via a simple USB-C connection on mobile or desktop applications and eliminate the need for additional technical training, special software or plant network permissions.



Rundown Phase	Tightening Phase	Tool Parameters
Tightening direction: Choose between clockwise or counterclockwise Speed (RPM): Set the free tool speed before shift-down conditions are met Angle shift down: Define the shift from the rundown to tightening phase based on the predefined value of angle rotation, up to 18,000° Time shift-down: Define the shift from the rundown to tightening phase based on a specific time duration up to 3 seconds	Speed (Programmable RPM): Tool speed is set to a user-defined value after high speed rundown, based on the specific shift-down conditions, ensuring precise and controlled tightening Rehit Detection Mode: Alert the operator that a fastener was previously tightened or has been cross-threaded.	Restart delay on OK cycle: Set a time interval to lock the tool after an OK tightening cycles Restart delay on NOK cycle: Set a time interval to lock the tool after a NOK tightening cycle Soft start (speed ramp up): The tool gradually ramps up at the beginning of a cycle Reverse disable: The tool only operates in the tightening direction


Rehit Detection Mode: When the tool detects a high load on a fastener at startup, Rehit Detection Mode immediately shuts off the tool, displays a cycle-fail indicator, alerting the operator that a fastener was previously tightened or has been cross-threaded.

Benefit: During a common fastening, there is a period of rundown during which the fastener encounters very little resistance. If high resistance is encountered at this stage, the fastener may have been tightened already, or the fastener has been cross-threaded. With Rehit Detection Mode enabled, the tool shuts down when it senses high resistance and will alert the operator that the fastener needs attention.




Soft-Start: The tool speed gradually ramps up at the beginning of a cycle.

Benefit: A gradual speed increase during soft start gives the operator more control as they get the fasteners started.



Tightening Direction: Can be programmed as clockwise or counter-clockwise to fasten joints.

Benefit: Tool can be operated in both clockwise and counterclockwise direction when in a shut-off mode.




Reverse Disable: The tool only operates in the tightening direction.

Benefit: Maintain control in production when operators are only required to install fasteners. When Reverse Disable is on, the tool will only operate in the tightening direction. Therefore, the tool cannot be used for fastener removal or for rework.



ADVANCED FEATURES



Restart Delay in OK/NOK Cycles: The Restart Delay function (also known as Rehit Prevention Mode) locks the tool, which disables the trigger for a specified period of time, and prevents operation when running an OK or NOK Tightening Cycle.


Benefit: Operator error can be lessened, especially during rapid tightening of a series of fasteners, when failure to advance to the next fastener or tightening of the same fastener twice may occur.

Programmable RPM: Set tool to shift down from **Run-Down Phase** to **Tightening Phase** based on a pre-defined shift down condition.

Angle shift down: Predefined value of angle rotation, up to 18,000°

Time shift-down: Predefined value of specific time duration up to 3 seconds

Benefit: Programmable RPM reduces risk of overtorquing. Damage to the workpiece is minimized when slower speed is used toward the end of the fastening process.



TECHNICAL SPECIFICATIONS

Specifications

Model	Tool Configuration	Drive	Torque Range (Nm)	Speed (RPM)	Weight w/o Battery (kg)	Length w/o Battery (mm)	Height w/o Battery (mm)
QCP2P02Q4	Pistol	1/4 Hex	0.5-2	350-1160	1.04	210	208.6
QCP2P04Q4	Pistol	1/4 Hex	1-4	350-1160	1.04	210	208.6
QCP2P08Q4	Pistol	1/4 Hex	3-8	140-700	1.04	210	208.6
QCP2P12Q4	Pistol	1/4 Hex	5-12	140-700	1.04	210	208.6
QCP2A30S6	Angle	3/8 Sq	15-30	60-300	1.59	510	66.3

All tool boxes include: Tool, clutch adjustment tool, protection boot, tool hanger, calibration certification and manuals.

Kits

EMEA	INDIA	Description
QCP2P02Q4-K2-EU	QCP2P02Q4-K2-IN	2 Nm Pistol – 2 Battery / 1 Charger Kit
QCP2P04Q4-K2-EU	QCP2P04Q4-K2-IN	4 Nm Pistol – 2 Battery / 1 Charger Kit
QCP2P08Q4-K2-EU	QCP2P08Q4-K2-IN	8 Nm Pistol – 2 Battery / 1 Charger Kit
QCP2P12Q4-K2-EU	QCP2P12Q4-K2-IN	12 Nm Pistol – 2 Battery / 1 Charger Kit
QCP2A30S6-K2-EU	QCP2A30S6-K2-IN	30 Nm Angle – 2 Battery / 1 Charger Kit



Battery and Charger Platform

IQV20™ Series 20V, 2.5 Ahr - Lithium-Ion Battery
BL2012



IQV20™ Series 20V
Single Battery Charger
BC1121-AP2 (For India)
BC1121-EU (For EMEA)



IQV20™ Series 20V, 5.0 Ahr - Lithium-Ion Battery
BL2022






IQV20™ Series 20V
Dual Bay Battery Charger
BC1221-IN (For India)
BC1221-EU (For EMEA)



QC SERIES

CLUTCH TOOLS

SIMPLY PRECISE



Learn more at www.irtools.com

Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.